

1.9

SAFETY DATA SHEET

B-10751M/ F220044

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

Business Phone/email: 1-800-487-7273 prousso@helenoftroy.com

SDS Revision: 5.0 SDS Revision Date: 5-17-2023

	1. PRODUCT & COMPANY IDENTIFICATION				
1.1	Product Name:	Drybar Detox Thickening Dry Shampoo			
1.2	Chemical Name:	Aerosol Powder Spray			
1.3	Synonyms:	Detox Thickening Dry Shampoo			
1.4	Trade Names:	Detox Thickening Dry Shampoo			
1.5	Product Uses/ Restrictions	Professional and Cosmetic Use / F220044			
1.6	Supplier Name:	Drybar Products LLC/Helen of Troy			
1.7	Supplier Address:	1 Helen of Troy Plaza, El Paso, TX 79912			
1.8	Emergency Phone:	VELOCITYEHS (CHEMTEL) 1-800-255-3924			

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)

WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. CAUSES EYE IRRITATION.

<u>Classification:</u> Aerosol level 2; Category 2 Flammable aerosol; Eye Irrit. 2; Gases Under Pressure-Liquified Gas

<u>Hazard Statements</u> (H): H-223–Flammable Aerosol. H229–Pressurized container: may burst if heated. H320 – Causes eye irritation. H280 – Contains gas under pressure; may explode if heated – liquified propellant, <u>Precautionary Statement</u> (P):

P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition source.

P251 – Do not pierce or burn, even after use.

P261 – avoid breathing vapors/spray.

P271 – Use only in well-ventilated area.

P304+P340 – IF INHALED; Remove person to fresh air and keep comfortable for breathing.

P305+P351+338 – IF INEYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present, continue rinsing.

P337+P313 – If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do no expose to temperature exceeding 48°C (120 °F).

P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.







3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
DIFLUOROETHANE (R-152a)	75-37-6	200-866-1	20 - 40	Flam. Gas 1; H220
BUTANE	106-97-8	203-448-7	20 - 40	Press. Gas 1; Flam. Gas 1; H220
Ethanol (SD Alcohol 40B)	64-17-5	200-578-6	10 - 30	Flam. Liq. 2; H225

4. FIRST AID MEASURES

			TITIOT / NO INC/ SOILES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		Eyes:	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.

B-10751M/ F220044

' .1	Work & Hygiene Practices	container(s).	When used as intended, no additional protective equipssible. Wash unintentional residues with soap and warr	ment is necessary. Use chemica						
			Irink, or smoke while handling this product. Contents ur		id puncturing					
		7	HANDLING AND STORAGE INFORM	ATION						
		done with m	inimal risk. Wear appropriate protective equipment inc	luding respiratory protection as	conditions warrant					
		not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking material (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container. Large spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warra								
		<u>Small spills</u> Wear appropriate personal protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. I								
5.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE).								
		T-	6. ACCIDENTIAL RELEASE MEASUR							
			sition products and oxygen deficiencies.							
			-contained breathing apparatus to protect against poter							
			fire control or dilution from entering sewers, drains, drin rway. Firefighters must use full bunker gear including N							
			to cool fire-exposed surfaces and to protect personnel.	•	\checkmark					
	<u> </u>	demand_ an	d full protective gear. Keep containers cool until well af	ter the fire is out. Use						
.3	Firefighting Procedures:		e, wear MSHA/NIOSH approved self-contained breathing	apparatus (pressure-						
.2	Extinguishing Methods:		ool by spraying them with water until the fire has been e oam, CO ₂ , Dry Chemical	extinguisneu.	3					
			flammable liquids and/or exposed gases if exposed to the	· · · · · · · · · · · · · · · · · · ·						
			nerosols are bursting, stay clear until bursting is complet							
	•		uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when							
.1	Fire and Explosion Hazards:	Level 2 Aeros	sol (NFPA 30B). Aerosols may burst at temperatures abo	ove 120° F (48°C). Cool						
			5. FIREFIGHTING MEASURES							
		exacerbated		EYES SKIN						
			uch as bronchial asthma and/or bronchitis) may be	PROTECTIVE EQUIPMENT	В					
	7	Existing dern	natological conditions (such as eczema) and respiratory	PHYSICAL HAZARDS	0					
.,	Aggravated by Exposure	1	ting properties to eyes, respiratory system and skin.	FLAMMABILITY	3					
.6 .7	Target Organs: Medical Conditions	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' 	spiratory system. hazards may be delayed. Most common symptoms	HEALTH	1					
	Taurat Ourana	allergic derm								
1.5	Chronic Health Effects:	symptoms in	some sensitive individuals. May also induce skin sensiti							
_	Characia Haalth Effects		skin and mucous membrane of the eye and respiratory s	= = = = = = = = = = = = = = = = = = = =	-					
			or chronic health effects are expected to occur from a sir	ngle accidental ingestion. These	ingredients may b					
1.4	Acute Health Effects:		itation to eyes and skin near affected areas. Additionall dizziness, headaches and nausea.	y, nigh concentrations of vapors	can cause					
		Inhalation:	Symptoms of overexposure can include coughing, who							
		Eyes:	may cause mild eye irritation including stinging, water	ing and redness.						
			Overexposure in eyes, may cause redness, itching and		e to eyes) Contact					
		Skin:	skin reactions (e.g., rashes, welts, dermatitis) in some overexposure may include redness, itching, and irritat		5 OT SKIN					
		Ckin	t can cause allergio							
.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and cent							
_			drowsiness, dizziness, headaches, nausea).							
		Inhalation:	respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion difficulty breathing. Inhalation of concentrated vapors can cause nervous system depression (e.g.							
			Moderately irritating to the eyes. Vapors of this product may be moderately irritating to the nose, throat and other tissues of the							
		Eyes:								
		May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, der some sensitive individuals upon prolonged or repeated exposure.								
		Skin:	I may be initiating to skill. The product call cause allerg	· -	cito, acrinatitio, III					

B-10751M/ F220044

Storage and Handling:	Use and store in a cool, dry, we	ll-ventila								
	sunlight. Avoid temperatures a physical damage. To avoid unir	bove 120	°F (48°C	C). Keep a	way from ii	ncompatibl	e substa	nces. Pro	tect cor	
Special Precautions:	Spilled material may present a									
	8. EXPOSURE CON	TROL	S & P	ERSON	IAL PRO	DTECTIO	NC			
						OSHA		OTHER		
Ppm (mg/m ³)	Chemical Name(s)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
	Ethanol (SD Alcohol 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
	BUTANE	1000	NA	1000	NF	NF	800	NA	NA	
	` `	1000	NA	1000		NA		NA	NA	L
Ventilation & Engineering Controls										-
	handling. In instances where d protection is needed, use only p State regulations, or the Canad Canadian Provinces, EC membe	usts of the protection ian CAS S or States,	iis produ n author itandard or Austra	ct are geneized by 29 Z94.4-93 a alia.	erated, and CFR §1910 and applica	l respirator).134, appli ble standar	y cable U.S			
Eye Protection:	•			•		, 0			E	
Hand Protection:	None required under normal conditions of use. However, may cause skin irritation is some sensitive individuals. When handling large quantities (e.g., \geq 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.									
Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs.), eye wash station and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									
	9. PHYSICA	L & CI	HEMIC	CAL PR	OPERT	IES				
Appearance:	Aerosol, misty powder spray									
Odor:	Fresh Sweet odor									
Odor Threshold	NA									
pH:	NA									
	NA									
	NA									
•	20°E / 24°C\ TCC for propollant only 2E 6 0E /2 0C\ EDA mothod 1010 Concentrate only									
Upper/Lower Flammability	NA	it Offiy, 3	3.0 °F (Z	C) LFA III	etilou 1010	Concentra	ite Offiy			
	@ 20 °C (68° F) – Can pressure	not to ex	ceed 180) psig @ 5	5 °C (131 °F	12.4 bar				
	>1			- - -	i					
Relative Density:	0.85 – 0.95									
	Soluble									
	NA									
•	NA 									
Temperature. Viscosity:	Aerosol at ambient temperatur									
	i Aciosoi ai allibielli lellibeidlui	C .								
	Ventilation & Engineering Controls Respiratory Protection: Eye Protection: Hand Protection: Body Protection: Appearance: Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition	Ppm (mg/m³) Chemical Name(s) Ethanol (SD Alcohol 40B) BUTANE DIFLUOROETHANE (R-152a) Ventilation & Engineering Controls Respiratory Protection: Respiratory Protection: No special respiratory protection handling. In instances where diprotection is needed, use only state regulations, or the Canad Canadian Provinces, EC member of protection: None required under normal control be used when handling or using the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used work activities involving large of thoroughly with soap and wate the used water activities of the used when handling in instances where different products. P. PHYSICA P.	Ppm (mg/m³) Chemical Name(s) Ethanol (SD Alcohol 40B) BUTANE 1000 DIFLUOROETHANE (R-152a) Controls Ceneral mechanical (e.g., fans) or natural exhaust ventilation to effectively removative product. Respiratory Protection: Respiratory Protection: No special respiratory protection is requal handling. In instances where dusts of the protection is needed, use only protection state regulations, or the Canadian CAS SCanadian Provinces, EC member States, None required under normal conditions be used when handling or using large quantitie or impervious plastic gloves. Body Protection: No apron required under normal conditions sensitive individuals. When handling small 5 lbs.), eye wash station and deluge showork activities involving large quantities thoroughly with soap and water. P. PHYSICAL & CP Appearance: Aerosol, misty powder spray Odor: Odor Threshold NA PH: NA Melting/Freezing Point NA Melting/Freezing Point NA Melting/Freezing Point NA Melting/Freesung Point NA Meltin	Ppm (mg/m³) Chemical Name(s) Ethanol (SD Alcohol 40B) BUTANE DIFLUOROETHANE (R-152a) TLV STEL Ethanol (SD Alcohol 40B) DIFLUOROETHANE (R-152a) Tubolo NA Ventilation & Engineering Controls Respiratory Protection: Respiratory Protection: No special respiratory protection is required und handling. In instances where dusts of this produ protection is needed, use only protection author State regulations, or the Canadian CAS Standard Canadian Provinces, EC member States, or Austr. None required under normal conditions of use. It is be used when handling or using large quantities Hand Protection: None required under normal conditions of use. It is sensitive individuals. When handling large quantities or impervious plastic gloves. Body Protection: No apron required when handling small quantities of this produce in the produce	Ppm (mg/m³) Chemical Name(s) TLV STEL ES-TWA	Ppm (mg/m³) Chemical Name(s) TLV STEL ES-TWA ES-STEL	Ppm (mg/m³)	Ppm (mg/m³) Chemical Name(s) Ethanol (SD Alcohol 40B) BUTANE BUTANE DIFLUGROETHANE (R-152a) 1000 NA 1000 NA 1000 NA NA NA NE Ventilation & Engineering Controls General mechanical (e.g., fans) or natural ventilation is sufficient when this product is interested in the product. Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR \$1910.134, applicable US state regulations, or the Canadian CAS Standard 294.493 and applicable standards of Canadian Provinces, EC member States, or Australia. Eye Protection: None required under normal conditions of use. Avoid eye contact. Safety glasses should be used when handling or using large quantities of this product (e.g., ≥1 gallon (3.8 L)), wear rubben intrile or impervious plastic gloves. Body Protection: No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubben intrile or impervious plastic gloves. Body Protection: No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubben intrile or impervious plastic gloves. Body Protection: PHYSICAL & CHEMICAL PROPERTIES Appearance: Aerosol, misty powder spray Physical & CHEMICAL PROPERTIES Appearance: Aerosol, misty powder spray Fresh Sweet dodr Odor Threshold NA NA Melting/Freezing Point NA Initial Boiling Point/ Boiling Range: Plashpoint: -30 °F (-34 °C) TCC for propellant only; 35.6 °F (2 °C) EPA method 1010 Concentrate only Upper/Lower Flammability Initial Boiling Point/ Boiling Range: Plashpoint: -30 °F (-34 °C) TCC for propellant only; 35.6 °F (2 °C) EPA method 1010 Concentrate only Upper/Lower Flammability NA Belative Density: Solublity: Partition Coefficient (log Pow): Autoignition Temperature: NA	Ppm (mg/m³) Chemical Name(s) TLV STEL ES-TWA ES-STEL ES-PEAK PEL STEL	Ppm (mg/m²)

B-10751M/ F220044

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-14-2023

		10. STABILITY & REACTIVITY						
10 1	Stability:	Stable at normal temperatures.						
	Hazardous Decomposition	Stable at normal temperatures.						
10.2	Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂)						
10.3	Hazardous Polymerization:	Will not occur.						
10.4	Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.						
10.5	Incompatible Substances	Mixture with strong acids, alkalis or oxidizers.						
		11. TOXICOLOGICAL INFORMATION						
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES						
11.2	·	This product was not tested on animals.						
	Acute Toxicity:	See Section 4.4						
11.4	·	See Section 4.5						
	Suspected Carcinogen:	NA						
	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.						
11.0	Mutagenicity:	This product is not reported to cause reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans.						
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.						
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.						
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.						
11 7	Irritancy of Product:	See Section 4.3						
		See Section 4.3						
11.8	"	NA NA						
11 0	Indices:							
11.9	Physician	Treat symptomatically.						
	Recommendations:							
		12. ECOLOGICAL INFORMATION						
12.1	,	There is no specific data available for this product.						
12.2		There is no specific data available for this product.						
12.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.						
		13. DISPOSAL CONSIDERATIONS						
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and						
		appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with						
		local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility						
		or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.						
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)						
44.	40 CED (CVID)	14. TRANSPORTATION INFORMATION						
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or						
		CONSUMER COMMODITY						
14.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or						
		ID8000, CONSUMER COMMODITY						
	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)						
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"						
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L)						
	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL < 1.0 L)						
	ADGR (AUS):	A TOUR SOUTH CONTINUES CHANGE OF THE PARTY O						
14./		UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)						

B-10751M/ F220044

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-14-2023

		15. REGULATORY INFORI	MATION					
	SARA Reporting Requirements:	This product does not contain any substance subject to S	ATA Title III, section 313 reporting requirements.					
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the	he components of this product.					
	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.						
15.4	CERCLA Reportable Quantity (RQ):	There are no specific Reportable Quantity						
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G. (Cosmetics)						
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List. WHMIS Class B5 (Flammable Aerosol)						
15.7	State Regulatory Information:	state criteria lists: California Proposition 65 (CA65), Delaw List (FL), Massachusetts Hazardous Substances List (MA),	MA, MN, PA, WA and NJ ria lists: MA and NJ tration of 1.0% or greater, are listed on any of the following ware Air Quality Management List (DE), Florida Toxic Substance Michigan Critical Substances List (MI), Minnesota Hazardous , New York Hazardous Substances List (NY), Pennsylvania Right					
15.8	Other Requirements:	The primary components of this product are listed in Ann Butane: Flammable (F+). Risk Phrases (R) 12 – Highly Fl Keep out of reach of children. Keep cool store below 120 – No smoking. Avoid exposure – obtain special instruction unwell seek medical advice immediately Ethanol: Flammable (F). Risk Phrases (R): 11 – Flammable children. Keep container tightly closed. Keep away from second container tightly closed.	nex I of EU Directive 67/548/EEC: lammable. Safety Phrases (S): 2-6-16 –53-45 D °F (48.8 °C). Keep away from sources of ignition n before use. In case of accident or if you feel e. Safety Phrase (S): 2-7-16 – Keep out of reach of					
		16. OTHER INFORMA	TION					
16.1	Other Information:	and other ignition sources. No Smoking. Do not spray or even after use. Avoid breathing vapor/spray. Wash thor ventilated area. Wear eye protection. Protect from sunl INHALED: Remove person to fresh air and keep comforta	TION. Keep away from heat, hot surfaces, sparks open flames in an open flame or other ignition source. Do not pierce or burn roughly with soap and water after handling. Use only in a well light. Do not expose to temperature exceeding 48°C (120°F). If able for breathing. IF IN EYES: Rinse cautiously with water for asy to do. Continue rinsing. If eye irritation persists: Get					
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.						
	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of voyant beauty's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.						
16.4	Prepared By:	Voyant Beauty 2030 Od Candler Road Gainesville, GA 30507 http://www.voyantbeauty.com	VOYAnt solutions driven by innovation					

B-10751M/ F220044

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0 SDS Revision Date: 4-14-2023



B-10751M/ F220044

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4-14-2023

